IN THE CLAIMS

Please amend the claims as follows:

Claims 1-12 (Cancelled)

Claim 13 (Currently Amended): A process for producing hydrogen, comprising: desulfurizing a hydrocarbon fuel by contacting the hydrocarbon fuel to an adsorbent

comprising cerium oxide, primary particles of the cerium oxide having a mean crystallite size

of 10 nm or less; and

subsequently bringing the desulfurized fuel into contact with a catalyst comprising at least one member selected from the group consisting of a partial-oxidation reforming catalyst,

an autothermal reforming catalyst, and a steam reforming catalyst;

wherein desulfurizing the hydrocarbon fuel comprises desulfurizing at room

temperature.

Claim 14 (Previously Presented): The process of claim 13, wherein the catalyst

comprises at least one member selected from the group consisting of ruthenium and nickel.

Claim 15 (Previously Presented): The process of claim 13, wherein desulfurizing is

performed without adding hydrogen or oxygen.

Claim 16 (Previously Presented): The process of claim 13, wherein desulfurizing

comprises removing at least one sulfur compound selected from the group consisting of

carbonyl sulfide, carbon disulfide, hydrogen sulfide, mercaptans, sulfides, and thiophenes.

Claims 17-18 (Cancelled)

2

Claim 19 (Currently Amended): A fuel cell system, comprising:

a desulfurizer; and

a reforming apparatus;

wherein:

the desulfurizer comprises an adsorbent comprising cerium oxide having primary particles with a mean crystallite size of 10 nm or less, the desulfurizer being configured so that a hydrocarbon fuel can be contacted to the adsorbent; and

the reforming apparatus comprises a catalyst comprising at least one member selected from the group consisting of a partial-oxidation reforming catalyst, an autothermal reforming catalyst, and a steam reforming catalyst, the reforming apparatus being configured so that a desulfurized fuel can be contacted to the catalyst;

wherein the desulfurizer is configured to desulfurize the hydrocarbon fuel at room temperature.

Claim 20 (Previously Presented): The process of claim 13, wherein the adsorbent has a specific surface area of $20 \text{ m}^2/\text{g}$ or more.

Claim 21 (Previously Presented): The process of claim 13, wherein the adsorbent has a specific surface area of $50 \text{ m}^2/\text{g}$ or more.

Claim 22 (Previously Presented): The process of claim 13, wherein the cerium oxide exhibits a cumulative hydrogen consumption, as calculated up to 600°C in a temperature-programmed reduction test, of 200 µmol/g or more.

Claim 23 (Previously Presented): The process of claim 13, wherein the cerium oxide exhibits a cumulative hydrogen consumption, as calculated up to 600° C in a temperature-programmed reduction test, of 300 μ mol/g or more.

Claim 24 (Previously Presented): The process of claim 13, wherein the adsorbent contains a mixture of cerium oxide and at least one oxide selected from the group consisting of Al₂O₃, SiO₂, TiO₂, ZrO₂, and MgO.

Claim 25 (Previously Presented): The process of claim 13, wherein: the adsorbent further comprises at least one element selected from the group consisting of elements belonging to Groups 1 to 15 in the periodic table; and the at least one element is carried on cerium oxide.

Claim 26 (Previously Presented): The process of claim 25, wherein the cerium oxide on which the at least one element is carried is calcined at a temperature of 400°C or less.

Claim 27 (Previously Presented): The process of claim 25, wherein the at least one element is present in an amount of from 1 to 90 mass% based on a total mass of the adsorbent.

Claim 28 (Previously Presented): The process of claim 13, wherein the cerium oxide is a complex oxide comprising cerium and at least one metallic element other than cerium

Application No. 10/526,397

Reply to Office Action of December 11, 2006

selected from the group consisting of elements belonging to Groups 2 to 16 in the periodic

table.

Claim 29 (Currently Amended): The process of claim 13, wherein the hydrocarbon

fuel is selected from the group consisting of LPG, town gas, natural gas, naphtha, kerosene,

gas oil, or at least one hydrocarbon compound or oxygen-containing hydrocarbon compound

selected from among ethane, ethylene, propane, propylene, butane, butene, methanol, and

dimethyl ether.

5